



UC36 Series

Low Friction Compact Piston Seal



FKM/FPM 75 PHYSICAL PROPERTIES

Working Pressure: ≤ 1.2 Mpa

Working Temperature: $-20^{\circ}\text{C} \sim +225^{\circ}\text{C}$

Surface Speed: ≤ 1.0 m/s

Hardness	75	Shore A	DIN53505
Tensile Strength	15.3	Mpa	DIN53504
	2214	psi	ASTM D-412
Elongation	241	%	DIN53504
Compression Set	9	%	DIN53517
22hrs @ 200°C	9	%	ASTM D-395
Standard Compound	V7514AA		
Color	Black ●		

NBR 75 PHYSICAL PROPERTIES

Working Pressure: ≤ 1.0 Mpa

Working Temperature: $-25^{\circ}\text{C} \sim +100^{\circ}\text{C}$

Surface Speed: ≤ 1.0 m/s

Hardness	75	Shore A	DIN53505
Tensile Strength	22.8	Mpa	DIN53504
	3306	psi	ASTM D-412
Elongation	320	%	DIN53504
Compression Set	10.9	%	DIN53517
24hrs @ 100°C	10.9	%	ASTM D-395
Standard Compound	N7539AA		
Color	Black ●		

CODE	D (mm)	d (mm)	L	H
UC36001	12.0	7.0	2.5	2.2
UC36002	16.0	9.0	2.5	2.4
UC36003	20.0	13.0	2.5	2.3
UC36004	25.0	18.0	2.5	2.4
UC36005	30.0	21.0	3.0	2.9
UC36006	32.0	23.0	3.0	2.9
UC36007	35.0	26.0	3.0	2.9
UC36008	40.0	31.0	3.0	2.9
UC36009	42.0	35.0	2.5	2.4
UC36010	45.0	36.0	3.0	2.8
UC36011	50.0	41.0	3.0	2.9
UC36012	60.0	48.0	4.0	3.9
UC36013	63.0	51.0	4.0	3.9
UC36014	70.0	58.0	4.0	3.9
UC36015	80.0	68.0	4.0	3.9
UC36016	100.0	88.0	4.0	3.9
UC36017	125.0	110.0	5.0	4.9
UC36018	90.0	78.0	3.9	3.8